



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
|-----------------|-------------|----------------------|---------------------|------------------|

10/681,081

10/08/2003

Teruhiko Ueyama

B588-555 (25815.567)

6248

26272 7590 08/21/2009
COWAN LIEBOWITZ & LATMAN P.C.
JOHN J TORRENTE
1133 AVE OF THE AMERICAS
NEW YORK, NY 10036

EXAMINER

MISLEH, JUSTIN P

ART UNIT

PAPER NUMBER

2622

MAIL DATE

DELIVERY MODE

08/21/2009

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

| | | | |
|------------------------------|--------------------------------------|---|--|
| Office Action Summary | Application No. 10/681,081 | Applicant(s) UEYAMA, TERUHIKO | |
| | Examiner JUSTIN P. MISLEH | Art Unit 2622 | |

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 07 July 2009.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1 - 7 and 9 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1 - 7 and 9 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 08 October 2003 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on July 7, 2009 has been entered.

Response to Arguments

2. Applicant's arguments filed July 7, 2009 have been fully considered but they are not persuasive.

Applicant states, "in the Noriyuki reference, whether or not to correct the exposure error is determined in accordance with the sensed image, not in accordance with whether or not the image sensing apparatus, which is in an image sensing operation, satisfies a predetermined condition."

Applicant subsequently concludes, "Thus, the Examiner's argument that the Noriyuki reference teaches that exposure error correction is determined based whether or not the image sensing apparatus satisfies a predetermined condition is incorrect and not supported by the reference teachings."

In response thereto, the Examiner respectfully notes Applicant has not provided any substantial reasoning to support the conclusion. Applicant simply concludes that determining

Art Unit: 2622

whether or not to correct the exposure error in accordance with the sensed image is not the same as being in accordance with the image sensing apparatus. For this reason alone, the Examiner will maintain the rejection.

3. However, the Examiner further notes that the main purpose of Noriyuki's invention is to provide an image pickup device that produces an image with correct exposure. See paragraph 0010. In both Noriyuki's auto-exposure and manual exposure modes, an image with correct exposure is produced. See paragraphs 0050 – 0054. Thus, in the case of Noriyuki, determining exposure correction in accordance with the image sensing apparatus satisfying a predetermined condition is contingent on the fact that Noriyuki determines whether or not to correct the exposure error is determined in accordance with the sensed image.

4. For these reasons, the Examiner will maintain the rejection of independent Claims 1 and 7 under 35 U.S.C. 102(b) as being anticipated by Noriyuki (JP 2000-069356 A).

5. Finally, it is noted Applicant provides several arguments against Kubo in view of Claims 1 and 7; however, these arguments are irrelevant as Kubo was not used in the rejection of Claims 1 and 7.

Claim Rejections - 35 USC § 102

6. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Art Unit: 2622

7. **Claims 1, 4, 5, 7, and 9** are rejected under 35 U.S.C. 102(b) as being anticipated by Noriyuki (JP 2000-069356 A).

8. For the following rejections, the Examiner will rely upon a computer translation of Noriyuki. Additionally, Claims 1 and 7 appear to be corresponding apparatus and method claims – accordingly, they will be rejected together. Finally, the Examiner’s response to arguments above is fully incorporated in the rejections below.

9. For **Claims 1 and 7**, Noriyuki discloses, an image sensing apparatus comprising:

a first exposure level calculation device (drawing 5, exposure control value operation part 201) which performs photometry for image sensing to calculate a first exposure level (page 6, paragraph 35, noted that 201 computes an exposure control value using the photometry data inputted from the photometry section) upon an image sensing preparation instruction by an image sensing preparation instruction member (drawing 5, shutter carbon button 9, page 6, paragraph 38, noted that when the shutter button is pushed, control section 20 drives the photometry section 3 to carry out the exposure control value operation, which is the exposure calculation);

a second exposure level calculation device (drawing 5, exposure level operation 202) which calculates a second exposure level (page 6, paragraph 36, noted that 202 computes the exposure level of the photographed image.) of an image signal output after image sensing;

a determination device (control section 20; see paragraph 0033) which determines whether or not to correct the exposure error (page 6, paragraph 36, noted that 203 calculates the gain alpha for amending the exposure level by comparing the data obtained from 201 and 202) in accordance with whether or not said image sensing apparatus, which is in an image sensing

Art Unit: 2622

operation, satisfies a predetermined condition (A test is performed in paragraph 0053 to decide whether correction should be made) when said image sensing apparatus is in auto exposure control mode (see paragraph 36 and 50), and;

an exposure error correction device (drawing. 5, level amendment section 19) which performs a correction operation of the exposure error (page 6, paragraph 33 and page 8, paragraph 54, noted that the 19 amplifies the level of each pixel data by gain alpha and performs level amendment of the image data) by using the exposure error calculated by said exposure error calculation device, when it is determined by said determination device to correct the exposure error (page 6, paragraph 33, noted that level amender 19 performs level amendment based on the amendment gain 203 inputted from a control section 20).

Noriyuki discloses a situation where instead of an automatic exposure operation, a manual exposure operation is carried out by the photographer. Noriyuki states in this regard, “Since it extracts based on the photographic subject brightness B_vC and a value A_v and the exposure time T_v are set up when exposure level of an image pick-up image is not expressed and an error arises neither in the photometry value of the photometry section 3 nor exposure control of CCD 10 nor the throttling control of diaphragm 12 at the time of photography, naturally this exposure level $A_{ve}C$ serves as $A_{ve}C=K$ (correct exposure level) ... [however,] it is general for an error to arise with one which participates in exposure control in fact of elements, and to become $A_{ve}C!=K$... [the] gain alpha for exposure level amendment shows the signal amplification factor for performing level adjustment of exposure level so that it may become with $A_{ve}C=K$ in $A_{ve}C!=K$ ” (see Noriyuki, paragraph 0050, computer translation).

Art Unit: 2622

10. As for **Claim 4**, Noriyuki teaches the apparatus according to claim 1, the operation state (drawing 6 and page 6, paragraph 37, the flow chart of photography e actuation of the digital camera) of the image sensing apparatus includes a state in which an image sensing processing start instruction is received from an image sensing start instruction member (drawing 5, shutter carbon button 9) before an end (drawing 6, the operation state from #1 to #2 and page 6, paragraph 38, the shutter button is pushed at #1 before the completion of operation state #2) of a first exposure level calculation processing (drawing 6, photometry data #2, page 6 paragraph 38, photometry data is used to carry out the exposure control value operation 201) by said first exposure level calculation device (201) that Starts upon reception of an image sensing processing preparation start instruction (drawing 6, the operation state from #1 to #2 and page 6, paragraph 38, the shutter button is pushed at #1 to start the instruction and to change the operation state to #2) by the image sensing preparation instruction member (drawing 5, shutter carbon button 9), and when the image sensing processing start instruction is received before the end (drawing 6, the operation state from #1 to #2 and page 6, paragraph 38, the shutter button is pushed at #1 before the completion of operation state #2) of first exposure level calculation processing (drawing 6, photometry data #2, page 6 paragraph 38, photometry data is driven by control section 20 to carry out the exposure control value operation 201) by said first exposure level calculation device (201), an image is sensed at an exposure value (drawing 6, photometry data #2, photometry data is computed at this .state) obtained during first exposure level calculation processing, said exposure correction calculation device (drawing 5, the amendment gain operation 203) calculates the correction amount of the exposure error value (page 6, paragraph 36, noted that 203 calculates the gain alpha for amending the exposure level by comparing the

Art Unit: 2622

data obtained from 201 and 202) by using information in first exposure level calculation (201) so as to obtain a sensed image at correct exposure, and said exposure error correction device (drawing 5, level amendment section 19) corrects the exposure error of the sensed image by using the correction amount (page 6, paragraph 33 and page 8, paragraph 54, noted that the 19 amplifies the level of each pixel data by gain alpha and performs level amendment of the image data).

11. As for **Claim 5**, Noriyuki teaches the apparatus according to claim 4, wherein when the image sensing processing start instruction is received (page 6, paragraph 38, the shutter button is pushed at #1 to start the photography actuation of the camera) before the end (drawing 6, the operation state from #1 to #2 and page 6, paragraph 38, the shutter button is pushed #1 before the completion of operation state #2) of first exposure level calculation processing (drawing 6, photometry data #2, page 6, paragraph 38, photometry data is used to carry out the exposure control value operation 201) by said first exposure level calculation device (201), and the setting state of the image-sensing apparatus includes at least one of a state (drawing 6, operation state #8) in which an exposure correction value is set (page 8, paragraph 54, noted that control section 20 sets the gain alpha as the level amendment section 19), a state in which an exposure condition obtained by photometry is held, a state in which a photometry method is set to spot photometry, a state in which a manual exposure, mode is set, and a state in which a long shutter mode is set, exposure starts (drawing 6, #5 and page 7 paragraph 41, noted that the charge storage/exposure of CCDIO starts) after a correct exposure value is calculated (page 8, paragraph 54, noted that control section 20 sets the gain alpha as the level amendment section 19) at the end of calculation processing by said first exposure level calculation device (201).

Art Unit: 2622

12. As for **Claim 9**, Noriyuki teaches a computer-readable recording medium (drawing 5, image memory 18) characterized by recording a program (page 6, paragraph 34, noted that the control section 20 carries out the centralized control of the photography actuation of the camera and it consists of a microcomputer which executes the processes of the exposure calculation. Thus it is an inherent feature that these programs are stored in a computer-readable recording medium to be executed by the microcomputer) defined in Claim 7.

Claim Rejections - 35 USC § 103

13. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

14. **Claims 2 and 6** are rejected under 35 U.S.C. 103(a) as being unpatentable over Noriyuki (JP 2000-069356 A) in view of Kubo (US 7,030,911 B1).

15. As for **Claim 2**, Noriyuki teaches all claimed limitation with the exception that he does not explicitly teach the apparatus according to claim 1, wherein the setting state of the image sensing apparatus includes at least one of a state in which an exposure correction value is set, a state in which an exposure condition obtained by photometry is held, a state in which a photometry method is set to spot photometry, a state in which a manual exposure mode is set, and a state in which a long shutter mode is set, and when any one of the states is set, said exposure correction calculation device does not correct the exposure error.

Art Unit: 2622

In an analogous art, Kubo teaches a digital camera exposure control method comprises of a setting state (fig. 6 and col. 7 lines 15-20, noted that the flow chart depicts the operation state of the digital camera) of the image sensing apparatus includes at least one of a state in which an exposure correction value is set, a state in which an exposure condition obtained by photometry is held, a state in which a photometry method is set to spot photometry, a state in which a manual exposure mode is set, and a state in which a long shutter mode (col. 7 lines 48-56, noted that when S2 switch is not pressed and S1 switch continues being on for not less than the predetermine time, it is determined that the exposure time is long) is set, and when any one of the states is set, said exposure correction calculation device does not calculate the correction amount of the exposure error value (col. 7, lines 48-56, since that when the operation state is returned back to #5, the exposure control value #27 will not be carried out in use), and said exposure error correction device does not correct the exposure error (col. 7, lines 48-56, since that when the operation state is returned back to #5, the exposure control value #27 will not be carried out in use, thus there will be no correction amount be used to correct the exposure error) of the sensed image.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the device of Noriyuki by incorporating the method of setting the long exposure mode as taught by Kubo in order to have the advantage of power saving feature in preventing the execution of rest of the operation states.

16. As for **Claim 6**, Noriyuki teaches all the claimed limitation with the exception that he does not explicitly teach the apparatus according to claim 1, wherein, in an operation state in which an image sensing start instruction member is not pressed is held for not less than a given

Art Unit: 2622

threshold time after the image sensing preparation instruction member is pressed, said exposure correction calculation device does not calculate the correction amount of the exposure error value, and said exposure error correction device does not correct the exposure error of the sensed image.

In an analogous art, Kubo teaches a digital camera exposure control method comprises of an operation state (fig. 6 and col. 7 lines 15-20, noted that the flow chart depicts the operation state of the digital camera) in which an image sensing start instruction member (fig. 6, S2 switch #23) is not pressed is held for not less than a given threshold time (col. 7 lines 48-56, noted that when S2 switch is not pressed and S1 switch continues being on for not less than the predetermine time, it is determined that the user has no intention to perform shooting and the processing state will return back to state #5) after the image sensing preparation instruction member is pressed (fig. 6, S1 switch #17, col. 7 lines 49-51, S1 switch is on), said exposure correction calculation device does not calculate the correction amount of the exposure error value (col. 7, lines 48-56, since that when the operation state is returned back to #5, the exposure control value #27 will not be carried out in use), and said exposure error correction device does not correct the exposure error (col.7, lines 48-56, since that when the operation state is returned back to #5, the exposure control value #27 will not be carried out in use, thus there will be no correction amount be used to correct the exposure error) of the sensed image.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to modify the device of Noriyuki by incorporating the method of setting the threshold time for the shutter switch button in controlling the operation state as taught by Kubo

Art Unit: 2622

in order to have the advantage of power saving feature in preventing the execution of rest of the operation states.

17. **Claims 3** are rejected under 35 U.S.C. 103(a) as being unpatentable over Noriyuki (JP 2000-069356 A) in view of Numata et al. (US 6,654,062 B1).

18. As for **Claim 3**, Noriyuki teaches all the claimed limitation with the exception that he does not explicitly teach the apparatus according to claim 1, wherein the setting state of the image sensing apparatus includes a state in which a flash is so set as to emit light, and when the flash is so set as to emit light, a correction width of the correction amount of the exposure error value is changed in consideration of at least one of a flashlight amount, a distance to an object, a stop state, and a setting sensitivity.

In the same field of endeavor, Numata teaches an electronic camera comprises a flash unit. Wherein, he discloses a state (col. 5, line 43, flash exposure mode) in which a flash is so set as to emit light (col. 6, lines 50-55, noted that flash exposure is performed), and when the flash is so set as to emit light, a correction width of the correction amount of the exposure error value is changed (col. 6, lines 55-60, noted that the aperture, shutter speed and gain amplifier are changed according to the value of optimum flash exposure) in consideration of at least one of a flashlight amount (col. 6, lines 50-55, noted that the optimum flash exposure is computed), a distance to an object, a stop state, and a setting sensitivity.

Therefore, it would have been obvious to a person of ordinary skill in the art at the time of the invention to incorporate the state of performing flash exposure as taught by Numata in Noriyuki's device in order to adjust the aperture of iris, shutter speed and gain values

Art Unit: 2622

corresponding to the change of the flash amount (col. 6, lines 50-60, noted that these parameters change based on the value of optimum flash exposure).

Conclusion

Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Justin P Misleh whose telephone number is 571.272.7313. The Examiner can normally be reached on Monday through Friday from 8:00 AM to 5:00 PM.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's supervisor, Jason Chan can be reached on 571.272.3022. The fax phone number for the organization where this application or proceeding is assigned is 571.273.8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

**/Justin P. Misleh/
Primary Examiner
Group Art Unit 2622
August 21, 2009**